

QuantaGrid S31A-1U

Energy Efficient, Compact 1U Architecture Envisioned for Performance and Large Storage Capacity in Space Constrained Data Centers



The QuantaGrid S31A-1U is a one-socket, 1U server tailored for applications requiring large local storage, scalable I/O, entry-level computing and high availability in space-constrained datacenters.

Energy Efficiency without Compromising Performance

Based on the Intel® Xeon® processor E3-1200 v5 product family in combination with DDR4 memory implementation, the QuantaGrid S31A-1U delivers a computing performance improvement of 10% and memory performance enhancement of 33% over the previous generation server. The maximum memory capacity also has been improved to 64GB while power consumption has been reduced by 20%. As a result, the QuantaGrid S31A-1U provides superior performance while simultaneously lowering operating costs of the data center.


Ultra Dense Chassis and Power Loss Protection Design

The QuantaGrid S31A-1U supports a CPU socket, 4x DRAMs, 1x PCIe expansion device, 1x OCP expansion device and redundant PSUs in a compact, 1U 24" depth chassis. As a compact size form factor server, this elegant, flexible architecture can be deployed in almost any SMB or data center environment. A reliable, redundant power supply design keeps the system consistently dependable and protects against power supply loss, device damage, and human negligence.

Hybrid Storage Solution and Flexible Options for Boot-up or Caching.

The QuantaGrid S31A-1U has 4x 2.5"/3.5" hot

- Hybrid Storage Solution
- Ultra Dense Chassis Design
- Enterprise-grade Internal Boot Device
- Flexible and Scalable I/O Options



swappable SATA/SAS HDD bays and 2x additional fixed 2.5" SAS/SATA SSDs. With the flexible options of the outstanding 2x 2280 M.2 equipped on the motherboard, the QuantaGrid S31A-1U can easily configure for extremely fast boot-up (SATA M.2) or high-performance data-caching (PCIe M.2) to meet the specific requirements of data center workloads.

Flexible and Scalable I/O options

The QuantaGrid S31A-1U offers flexible I/O scalability for today's diverse data center application requirements. It features OCP LAN mezzanine card solutions in addition to dual GbE LAN on motherboards (LoM). With various controller selections and different speed and technology options from 1GbE to 56GbE bandwidth, copper or fiber-optic cabling, basic Ethernet function or FCoE and ISCSI SAN connectivity.

About QCT

QCT (Quanta Cloud Technology) is a global datacenter solution provider extending the power of hyperscale datacenter design in standard and open SKUs to all datacenter customers.

Product lines include servers, storage, network switches, integrated rack systems and cloud solutions, all delivering hyperscale efficiency, scalability, reliability, manageability, serviceability and optimized performance for each workload.

QCT offers a full spectrum of datacenter products and services from engineering, integration and optimization to global supply chain support, all under one roof.

The parent of QCT is Quanta Computer Inc., a Fortune Global 500 technology engineering and manufacturing company.

<http://www.QCT.io>

QuantaGrid S31A-1U



Found at: www.QCT.io/wheretobuy

United States

QCT LLC., Silicon Valley office
1010 Rincon Circle, San Jose, CA 95131
TOLL-FREE: 1-855-QCT-MUST
TEL: +1-510-270-6111
FAX: +1-510-270-6161
Support: +1-510-270-6216

China

云达科技, 北京办公室
(Quanta Cloud Technology)
北京市朝阳区东三环中路 1 号
环球金融中心东楼 1508 室
TEL: +86-10-5920-7600
FAX: +86-10-5981-7958

云达科技, 杭州办公室

(Quanta Cloud Technology)
浙江省杭州市西湖区古墩路浙商财富中心 4 号楼
303 室
TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社
日本国東京都港区芝大門二丁目五番八号
牧田ビル 3 階
TEL: +81-3-5777-0818
FAX: +81-3-5777-0819

Taiwan

雲達科技 (Quanta Cloud Technology)
桃園市龜山區文化二路 211 號 1 樓
TEL: +886-3-286-0707
FAX: +886-3-327-0001

Other regions

Quanta Cloud Technology
No. 211 Wenhua 2nd Rd., Guishan Dist.,
Taoyuan City 33377, Taiwan
TEL: +886-3-327-2345
FAX: +886-3-397-4770

QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their representative holders.
Copyright © 2016 Quanta Computer Inc. All rights reserved.

Processor	Processor Type: Intel® Xeon® processor E3-1200 v5 product family Max. TDP Support: 80W Number of Processors: 1 L3 Cache: Up to 8MB
Chipset	Intel® C236
Memory	Total Slots: 4 Capacity: Up to 64GB UDIMM Memory Type: 2133 MHz DDR4 UDIMM Memory Size: 16GB, 8GB UDIMM
Network Controller	LOM: Intel® I210 dual-port 1 GbE Dedicated 1 GbE management port Optional NIC (more options refer to the CCL): QCT Intel® i350 dual-port OCP mezzanine QCT Intel® X540 dual-port 10GbE BASE-T OCP mezzanine QCT Intel® 82599ES dual-port 10G SFP+ OCP mezzanine
Storage Controller	Onboard: Intel® C236: (8) SATA 6Gb/s ports SATA RAID 0, 1, 5, 10 Optional Controller: QCT LSI® 3008 12Gb/s SAS mezzanine, RAID 0,1,10 QCT LSI® 3108 12Gb/s RAID mezzanine, RAID 0, 1, 5, 10; RAID 6 requires additional RAID key
Onboard Storage	(2) 2280 M.2
Video	Integrated AST2400 with 8MB DDR3 video memory
Rear I/O	(2) USB 3.0 ports (2) 1GbE RJ45 (1) 1GbE RJ45 management port (1) Console port on the system (1) VGA port
TPM	Yes (With TPM 1.2/ 2.0 option)
Form Factor	1U Rack Mount
Dimensions	W x H x D (inch): 17.2 x 1.7 x 24 W x H x D (mm): 438 x 43.2 x 609.2
Storage	(4) 3.5"/2.5" hot-plug HDD (2) 2.5" fixed SSD
Expansion Slot	(1) PCIe Gen3x8 Low profile MD-2 slot (1) PCIe Gen3x8 OCP mezzanine slot
Front I/O	(2) USB 2.0 ports
Power Supply	Option 1 : (2) 400W/700W High efficiency redundant hot-plug PSU Option 2 : (1) 500W fixed PSU (default with one PSU only; detailed PSU options please refer to "ordering info" or "CCL")
Fan	(3) dual rotor fans
System	IPMI v2.0 Compliant, on board "KVM over IP" support
Management	Quanta System Manager
Operating Environment	Operating temperature: 5°C to 40°C (41°F to 104°F) Non-operating temperature: -40°C to 65°C (-40°F to 149°F) Operating relative humidity: 20% to 85%RH. Non-operating relative humidity: 10% to 90%RH

Intel Inside®. Powerful Data Center Outside.

Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries.

