


NB1U-E3C242D4S Rack-mount Server

Specifications Table



PRODUCT HIGHLIGHTS



Support 1 x Intel® Xeon® E-22xx, Pentium, Core i3/i5 9th Gen Series Processor



Up to 4 x Hot-plug 2.5"/3.5" Disks + 2 x Fixed 2.5" Disks




Single Fixed or Redundant Hot-Plug Power Supply Unit



On-Board Intel® Rapid Storage RAID 0/1/5/10



KVM over IP Support



Form Factor	537.55 x 430 x 43.3mm
Processor	(1) Intel® Xeon® E-22xx, Pentium, Core i3/i5 9th Gen Series Processor
Chipset	Intel® C242 chipset
Memory	(4) DDR4 2666/2400 ECC UDIMM slots
Storage	(4) 3.5" Hot-plug disks (front bay) (2) 2.5" Fixed disks (internal) <i>* Support for SAS disk requires Add-on SAS card</i>
SATA Controller	Intel® C242 : 6 x SATA3 6.0Gb/s; support RAID 0, 1, 5, 10
Expansion Slot(s)	(1) PCIe 3.0 x8
Network	(2) Intel® i210 1GbE RJ45 port (1) Realtek RTL8211E 1GbE RJ45 Dedicated port for Management
Integrated Graphics	Aspeed AST2500 32MB DDR4 video memory
Rear I/O	(4) USB 3.2 Ports (1) VGA Port (2) 1GbE RJ45 Ports (1) Serial Port
Internal Cooling	(4) 40 x 28mm PWM easy-swap fans up to 14,500RPM
Power Supply	(1) Fixed 500W 80 PLUS Gold PSU or (2) Hot-Plug 300W 80 PLUS Gold PSU
Server Management	IPMI v2.0 compliant, on board "KVM over IP" support
Environment	Operating temperature: 10°C ~ 35°C / Non-operating temperature:-40°C ~ 70°C



Serveron Sdn Bhd

Unit C-6-15, Block C, Southgate Commercial Complex, No. 2, Jalan Dua, Chan Sow Lin, 55200 Kuala Lumpur, Malaysia

Main: 1-700-81-7837 Fax: +603-9226-0771

Email: sales@serveron.com.my For more information, please visit www.serveron.com.my

