


NB2U-ROMED8-2T 2U Rack-mount Server



PRODUCT HIGHLIGHTS



Support 1 x AMD EPYC™ 7002/7003 Series Processors



Up to 12 x Hot-plug 3.5" Disks + 2 x 2.5" Internal Disk Bays



Single Fixed or Redundant Hot-Plug Power Supply Unit



On-Board Intel® Rapid Storage RAID 0/1/10



KVM over IP Support

Form Factor	625 x 482.6 x 87mm
Processor	(1) AMD EPYC™ 7002/7003 Series Processors
Chipset	AMD SoC
Memory	(8) DDR4 3200/2933ECC RDIMM/LRDIMM slots
Storage	(12) 3.5" Hot-plug disks (front bay) (2) 2.5" Internal Fixed Disk bays
SATA Controller	AMD EPYC 7002
Expansion Slot(s)	(6) PCIe 4.0 x16 (1) PCIe 4.0 x8
Network	(2) Intel® X550 1/10GbE RJ45 port (1) Realtek RTL8211E 1GbE RJ45 Dedicated port for Management
Integrated Graphics	Aspeed AST2500
Rear I/O	(2) USB 3.2 Ports Type-A (1) USB 3.2 Port Type-C (1) VGA Port (2) 1/10GbE RJ45 Ports (1) 1GbE RJ45 Port (Management)
Front I/O	(2) USB 2.0 Ports
Power Supply	(1) Fixed 500W 80 PLUS Gold PSU or (2) Hot-Plug 800W 80 PLUS Platinum PSU
Server Management	IPMI v2.0 compliant, on board "KVM over IP" support
Environment	Operating temperature: 10°C ~ 35°C / Non-operating temperature: -40°C ~ 70°C



Serveron Sdn Bhd

Unit C-6-15, Block C, Southgate Commercial Complex, No. 2, Jalan Dua, Chan Sow Lin, 55200 Kuala Lumpur, Malaysia

Main: 1-700-81-7837 Fax: +603-9226-0771

Email: sales@serveron.com.my For more information, please visit www.serveron.com.my